

SUNDANCE 780 & SELECT SERIES SPA CHEMICAL GUIDE – GRANULAR DICHLOR CHLORINE

SUPERIOR WANTS YOU TO THOROUGHLY ENJOY YOUR NEW SPA.

THESE INSTRUCTIONS ARE BASED ON THE GUIDELINES FOR SPAS ESTABLISHED BY THE

ASSOCIATION OF POOL & SPA PROFESSIONALS

WARNING....If you do not follow these instructions you may be endangering your family's health!

DO THIS EVERY TIME YOU FILL YOUR HOT TUB

- By-pass your water softener systems to avoid damaging your spa water heater
- Remove filter and fill spa through filter well
- Test and balance PH to (7.2 to 7.6) Alkalinity to (80 to 120 PPM) and using increments of 1 oz of PH Up or PH Down as needed
- Add 4 oz. of Stain & Scale and 5 oz. of Natural Spa Enzyme...
 Wait 4 hours before adding Chlorine
- Bring Chlorine Level up to 10 Parts per million (ppm)
 Start with 3 heaping teaspoons of Granular Dichlor Chlorine.
 Add Granular Dichlor Chlorine in increments of 1 heaping teaspoon until chlorine level of 10 ppm is achieved
- Wait 24 hours before using Spa

DAILY MAINTAINANCE

- Test water to ensure a chlorine level of 3 ppm
 Chlorine should be added at a minimum of every 3 days even if spa will not be used!!!!
- Add Chlorine in increments of 1 heaping teaspoon at a time in order to maintain proper chlorine level
- **Heavy Usage** Additional Chlorine may be needed ... Test frequently
- Test and balance PH to (7.2 to 7.6) Alkalinity to (80 to 120 ppm) using increments of 1 oz of PH Up or PH Down as needed

WEEKLY MAINTAINANCE

Open Cover & Turn Pumps on to High Speed

Add 3 heaping teaspoons of Spa Shock to running spa

Wait 5 Minutes...Turn Pump 1 to Low Speed

- Add 2 oz. Stain & Scale
- Add 5 oz. Natural Spa Enzyme

EVERY 3 MONTHS

FILTER MAINTENANCE

WARNING: Do not operate the spa without the filters in place!

Remove scum bugs or any other floating objects before removing the filters

Turn power off or put into L1 before removing filters

We recommend owning spare filters to alleviate down time

- Separate Micro Clean Filter from Large Filter and dispose of Micro Clean Filter
- Assemble clean Large Filter and new Micro Clean Filter and reinstall in spa
- Soak dirty Large Filter in water with 12 oz. of Filter Cleaner for 2 to 3 days
- · Rinse thoroughly with filter flosser
- Allow to air dry, store in a clean dry location
- Replace both Large Filters every 2 years (when alternating 2 filters)
- Replace **Micro Clean** every 3 months
- Do not ever soak Micro Clean filter in filter cleaning solution

EVERY 3 MONTHS

- Drain and refill your spa... Follow initial fill up procedure
- Power must be off when draining spa

FREEZE WARNING

- These statements do not apply to spas located in heated areas
- Do not drain and refill your spa if the air temperature is below 35 Degrees
- During freezing temperatures always check your spa east once every other day
- Freeze damage is not covered under warranty

AVOIDING CLOUDY WATER IN YOUR SPA

- Keep soap and detergent out of your spa
- Rinse all bathing suits by hand.
- Do not wear shorts, tee shirts, and cut-offs
- Rinse off all lotions, make up and skin care products
- Never use household cleaning products on your spa
- Maintain proper chemical balance

Chemical damage to covers and pillows is not covered by warranty

Leave cover open and run pumps for 5 minutes when adding spa shock or large amounts of chlorine to let gases escape

TO REORDER CHEMICALS & SUPPLIES & ACCESSORIES CALL:

SUPERIOR HEARTH, SPAS AND LEISURE

888-SPAS-288

WE WILL SHIP RIGHT TO YOUR DOOR